

## CLAIMS

Sub  
A1

1. Optical sight comprising:  
an elongate housing defining a light channel;  
a lens located at one end of the light channel and having a partially reflecting surface;  
a laser diode for emitting light towards said reflecting surface to produce a light spot by direct imaging of the said laser diode on said surface to be superimposed on a target when sighting through the light channel from the other end thereof;  
a battery for providing electric current; and  
an energising circuit for energising said laser diode, operable to apply a pulsating electric current from said battery to said laser diode source for causing the laser diode to emit pulses of light.

2. Optical sight as in claim 1 wherein control means are provided for adjusting the intensity of the light spot.

3. Optical sight as in claim 2 wherein said control means comprise pulse width modulation of the laser diode source.

Sub  
A2

4. Optical sight as in claim 1 wherein control means are provided for energising the laser diode when the weapon is to be used and for automatically reducing energisation of the laser diode in dependence of a predetermined condition.

A

5. Optical sight as in claim 4 wherein said control means comprises a switch for <sup>energizing</sup> ~~energising~~ the laser diode.

6. Optical sight as in claim 5 wherein said switch is a manually operated switch.

A

A

7. Optical sight as in claim 4 wherein said control means comprises a time-out circuit for <sup>deenergizing</sup> ~~deenergising~~ the laser diode a predetermined period after the laser diode <sup>has been energized</sup> ~~having been energised~~.

8. Optical sight as in claim 4 wherein said control means comprises a motion sensor for detecting vibration and motion of the sight when a weapon to which the sight <sup>is</sup> mounted being held by a user of the weapon and for ~~deenergizing~~ <sup>energizing</sup> the laser diode when no vibration and motion being detected.

9. Optical sight as in claim 4 wherein said control means comprises a sensor for detecting the orientation of a weapon to which the sight is mounted for ~~energizing~~ <sup>energizing</sup> the laser diode and maintaining the laser diode ~~energized~~ <sup>energized</sup> as long as the weapon is held by a user thereof in normal orientation of use.

10. Optical sight as in claim 4 wherein said control means comprises a sensor for detecting the presence of ambient light for ~~energizing~~ <sup>energizing</sup> the laser diode and maintaining the laser diode ~~energized~~ <sup>energized</sup> at lightness and reducing the ~~energizing~~ <sup>energizing</sup> of the laser diode in darkness.

11. Optical sight as in claim 4 wherein said control means comprises a sensor for detecting the presence of an eye looking through the sight, for ~~energizing~~ <sup>energizing</sup> the laser diode when an eye is looking through the sight and maintaining the laser diode ~~deenergizing~~ <sup>deenergizing</sup> in the absence of an eye looking through the sight.

12. Optical sight as in claim 4 wherein said control means comprises a detector for detecting a phenomenon associated with a human being for ~~energizing~~ <sup>energizing</sup> the laser diode when detecting said phenomenon and ~~deenergizing~~ <sup>deenergizing</sup> the laser diode in the absence of such phenomenon being detected.

13. Optical sight as in ~~any preceding~~ claim <sup>1</sup> wherein the wave length of the light emitted by the laser diode ranges from 630 to 700 nm.

add  
B2  
Add C1